



TARPS Inc.

TECHNICAL DATA

18oz. VINYL-TEX SPECIFICATIONS

<u>TEST</u>	<u>TEST METHOD</u>	<u>RESULT</u>
WIDTH	WIDTH	61 1/4"
BASE FABRIC - POLYESTER	BASE FABRIC - POLYESTER	1,000D X 1,300D 18 X 17
WEIGHT	FS-191-5041	18.5oz. / square yard
GRAB TENSILE STRENGTH	FS-191-5100	410lbs. x 410 lbs
STRIP TENSILE STRENGTH	FS-191-5102	300lbs. x 300lbs.
TRAPEZOID TEAR STRENGTH	FS-191-5136	30lbs. x 30lbs.
TONGUE TEAR STRENGTH	FS-191-5134	100lbs. x 100lbs.
ADHESION	FS-191-5970	12 x 10 lbs/inch
ABRASION RESISTANCE	FS-191-5306	400 cycles
HYDROSTATIC RESISTANCE	FS-191-5512	At least 600lbs. psi
COLD CRACK	FS-191-5874	-40 degrees F
U.V. RESISTANCE	WEATHER-O-METER	Not Excessive Fading After 300 Hours
HIGH TEMPERATURE RESISTANCE	FS-191-5872	180 degrees F (does not block)

****Please Note: Above values represent typical data and are subject to slight variations.
No warranty is expressed or implied regarding the accuracy of this data.**

Colors Available: Black, White, Charcoal, Gray, Tan, Brown, Burgundy, Red, Orange, Yellow, Green, Royal, Navy, Light Blue, Pink, Dark Purple

Common Uses: Tarps, General Purpose Covers, Enclosures, Flatbed Tarps, Lumber Tarps, Oil Rig Shelters, Industrial Fabric Products, Snow Tarps, Construction Tarps, Industrial Curtains, Gym Floor Covers, RV Skirts, Recreational Products, Inflatables, Tonneau Covers, Equipment Covers, Agricultural & Farm Bed Tarps, Hay Tarps